

## 'Y-TYPE' STRAINER SNP 50mm-300mm Cast Iron Flanged Strainer

### APPLICATION:

- Filters foreign bodies such as solid particles in a pipeline, to protect the water supply system.

### FEATURES:

- Improve quality the quality of water or other medium passing through the pipe.
- Easy installation and maintenance.
- Protects water meters, valves and other equipment installed within a pipeline, to prolong their service life.
- Customizable mesh of wire or the hole dimensions of the perforated screen.
- Cast Iron epoxy coated body. Face to Face dimensions according to DIN3202, F1.
- Flange dimensions according to DIN2501 PN10/PN16.
- Nominal Pressure: PN10/PN16.



### DIMENSIONS TABLE

Type	Size (mm)	L Length (mm)	H Height (mm)	Available Connecting Flange BS4505			± Weight (kg)
				D	D1	Z-Ød	
				Outside Diameter (mm)	Bolt Circle Diameter (mm)	Connecting Bolts	
SNP - 50	50	230	168	165	125	4-M18	10,78
SNP - 65	65	290	178	185	145	4-M18	15,3
SNP - 80	80	310	215	200	160	8-M18	20,2
SNP - 100	100	350	249	220	180	8-M18	26,8
SNP - 125	125	400	268	250	210	8-M18	37,1
SNP - 150	150	480	292	285	240	8-M23	56,1
SNP - 200	200	600	316	340	295	12-M23	90,6
SNP - 250	250	730	428	405	355	12-M27	143,7
SNP - 300	300	850	492	460	410	12-M27	184,6

### DIMENSIONS



